

DP721R

700 Series Conventional Optical Smoke Detector w/ Relay Output

Preventing false alarms with self diagnostics

All Aritech 700 series smoke detectors continuously monitor their sensitivity and operational status. Background drift is daily compensated to maintain the original calibrated sensitivity within the required limits.

Once a day the detector performs a full diagnostic test that includes dynamically testing the sensing chamber and internal electronics. If a detector drifts out of sensitivity range or fails the internal diagnostics test, this is reported back to the panel and indicated on the detector with a yellow fault LED.

Maintenance friendly sensitivity level test mode

The 700 Series photoelectric detectors include a sensitivity test mode that may be activated by simply holding a magnet near the detector's test point. This initiates a self-diagnostic routine and provides visual indication if service is required. This test mode allows field sensitivity testing without the requirement for external meters or test gas.

Field cleaning and service

The photoelectric sensing chamber unclips from the detector for easy field cleaning and service. During regular maintenance the detector cover can be removed, the optical chamber removed and replaced by a low cost, new chamber. On power up the detector auto-calibrates and returns to normal operating mode without any further intervention.

The right detector for the right job

For a truly fast and broad-spectrum detection the DP721RTA offers both optical and heat sensors. The interaction of both the smoke and heat algorithms ensure a quick response to both flaming and smoldering fires.

All bases are provided with an integral locking tab for extra security if required. Bases are equipped with a shorting bar between IN and OUT that opens when the head is installed and that may be manually restored when removing the head. This simplifies cable continuity testing.

Note:

The DP721RTA must not be used in applications requiring compliance with commercial or residential fire standards such as EN54-5/EN54-7/EN54-29/CEA4021/EN14604. Always ensure compliance with local codes and standards.



Details

- Automatic self diagnostics: Dynamic full detector and sensitivity test
- Manual self diagnostic with visual sensitivity indication
- Field sensitivity testing without external meters
- Field exchangeable and disposable optical chamber
- High false alarm immunity
- Floating background with drift compensation
- Separate fire and fault LED
- 12 - 24 VDC operation
- Polarity insensitive
- Full range: optical, heat and optical/heat multi criteria sensor
- EN54 approved and CPR certified

DP721R

700 Series Conventional Optical Smoke Detector w/ Relay Output

Technical specifications

Electrical

Operating voltage	8.5 to 33 VDC
-------------------	---------------

Physical

Physical dimensions	100 x 50 mm (Ø x H)
---------------------	---------------------

Colour	White
--------	-------

Environmental

Operating temperature	-10 to +60°C
-----------------------	--------------

Relative humidity	0 to 95% noncondensing
-------------------	------------------------

Environment	Indoor
-------------	--------

IP rating	IP43
-----------	------

Standards & regulation

Certification	EN54-7
---------------	--------

Operating voltage

8.5 - 33 VDC

Current consumption

Quiescent at 24 VDC	100 µA max.
---------------------	-------------

In alarm at 24 VDC	60 mA
--------------------	-------

Alarm indication

White LED (red alarm)

Fault indication

Yellow LED

Remote alarm output

30 mA

Relay models	2 A @ 30 VDC, 1 A @ 120 VAC
--------------	-----------------------------

Humidity

0 - 95%, Non-condensing

IP rating

IP43

Operating temperature

-10°C to 60°C

Sensitivity

10%/m (+1.6%, -3.3%)

Heat specification

Ambient	25°C
---------	------

R.O.R.	NA
--------	----

Fixed temp	NA
------------	----

Reset voltage

2.5 V max

Reset time

1 s

Dimensions

10 cm Ø, H = 5 cm

As a company of innovation, UTC Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit UTC Fire & Security online or contact your sales representative.

23 February 2019 - 12:41


engineering co. ltd.

 **United Technologies**
Climate | Controls | Security