

IU2050NC

2000 Series IO Unit 1 In

General

The IU2050NC is a 2000 series addressable single input unit with selectable line supervision to monitor normally open or normally closed contacts. The unit is loop powered and supplied in an enclosure for surface mounting applications.

The 2000 series loop powered input/output modules are designed to provide much needed flexibility to input monitoring and output switching. These modules, combined with the powerful features of the Aritech addressable fire panels, give the user versatility for diverse applications.


Applications

The addressability of the IU2050NC allows the identification of the exact location of the switch activation. It may be used with applications requiring fast response such as conventional manual call points, door monitors etc. where a change of state needs to be reported within 3 seconds. Alternatively it can be used in any application where a point needs to be made addressable and supervised on the fire panel.

Installation

The IU2050NC is connected to an Aritech CIE via a two-wire communication loop that provides power and control data. The single input module address is conveniently set with rotary switches. The address setting is non-volatile and will not be lost in the event of a power failure.

The single input module utilizes an advanced digital data communications protocol that ensures the integrity of the data communications with extensive error correction algorithms.



Details

- Loop powered
- Programmable input state
- Easy numeric addressing
- EN54 approved and CPR certified

IU2050NC

2000 Series IO Unit 1 In

Technical specifications

Electrical

Operating voltage	17 to 28 VDC
Current consumption	<205 μ A (Quiescent), <270 μ A (Active)
Communication voltage	4 to 10 V
Cable length to contact	< 10 m

Input

Input quantity	1
Input type and rating	Supervised
Termination	150 k Ω , ¼ W, 5%

General

Compatibility	2000 Series Systems
---------------	---------------------

Physical

Physical dimensions	120 x 90 x 35 mm
Net weight	144 g
Colour	Cool grey
Mounting type	Surface Mount
Cable entries	1

Environmental

Vandal proof	No
Operating temperature	-10 to +55°C
Storage temperature	-20 to +60°C
Relative humidity	10 to 95% noncondensing
Environment	Indoor
IP rating	IP40

Standards & regulation

Compliance	CE, REACH, RoHS 2
Certification	BOSEC, VdS
Standards	EN54-18

As a company of innovation, UTC Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit UTC Fire & Security online or contact your sales representative.

23 February 2019 - 8:54


engineering co. ltd.


Climate | Controls | Security