

DT2063N

2000 SERIES ADDRESSABLE HEAT DETECTOR W/ DUAL LED & REMOTE OUTPUT

General

The DT2063N is a 2000 series protocol, addressable heat detector certified to class A2R. It provides good looks as well as top features, including a rate-of-rise algorithm that allows the device to raise the alarm before the fixed temperature trigger point is reached. Dual fire LEDs indicate an alarm visible from all directions, eliminating the need for special detector orientation on installation, whilst a remote indicator output is provided as standard on every device.

Installation Friendly

The DT2063N is individually identified by setting an address through two rotary switches. The address is a straight numerical value and does not require binary or hexadecimal conversions, significantly reducing the risk of incorrect addressing.

All 2000 series detectors are compatible with a standard base that makes them easily interchangeable.

State of the Art Communication

Panel to device communication is provided through a powerful SIA protocol featuring multiple bus cycle codes and CRC error checking and ensuring reliable communications between the device and the control panel.

This enhanced protocol ensures the overall integrity and error free operation of the full system, without compromising speed.

Extended Applications

For varied applications the fixed temperature trigger level of the DT2063N may be set from the CIE to accommodate higher activation temperatures.

A comprehensive line of complimentary devices completes the 2000 series portfolio:

- common use detector bases
- optical, temperature and multi-sensors
- standalone and base isolators
- sounder circuit controllers
- conventional zone monitoring units
- various supervised and non-supervised I/O units
- a comprehensive line of manual call points
- loop powered notification devices and beam detectors



Details

- Dual thermistors
- Remote signaling capabilities
- Easy numeric addressing (1-128)
- Enhanced communication protocol
- Full diagnostic self testing
- Full range including optical and multi sensors
- Full range of I/O units and accessories
- Optional isolator base
- EN54:5 approved and CPR certified

DT2063N

2000 SERIES ADDRESSABLE HEAT DETECTOR W/ DUAL LED & REMOTE OUTPUT

Technical specifications

Electrical

Operating voltage	17 to 28 VDC
-------------------	--------------

Physical

Physical dimensions	100 x 50 mm (Ø x H)
---------------------	---------------------

Net weight	83 g
------------	------

Colour	Cloud white (RAL 9001)
--------	------------------------

Dimensions (Ø x h)	10 x 5 cm
--------------------	-----------

Colour	Cloud White (RAL9001)
--------	-----------------------

Weight	83 g
--------	------

Environmental

Operating temperature	-10 to +60°C
-----------------------	--------------

Storage temperature	-10 to +70°C
---------------------	--------------

Relative humidity	10 to 95% noncondensing
-------------------	-------------------------

Environment	Indoor
-------------	--------

IP rating	IP23
-----------	------

Humidity (noncond.)	10 - 95%
---------------------	----------

Storage temperature	-10°C to +70°C
---------------------	----------------

Operating temperature	-10°C to +60°C
-----------------------	----------------

IP rating	IP23
-----------	------

Standards & regulation

Certification	EN54-5
---------------	--------

Operating voltage

17 - 28 VDC

Current consumption

Quiescent @ 24 VDC	< 270 µA
--------------------	----------

Alarm @ 24 VDC	4.7 mA
----------------	--------

Alarm indication

Dual LED

Remote alarm output

4.7 mA

Coverage

Area	< 80 m ²
------	---------------------

Compliance

EN54-5

As a company of innovation, UTC Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit UTC Fire & Security online or contact your sales representative.

25 February 2019 - 6:26


engineering co. ltd.

 **United
Technologies**
Climate | Controls | Security