


ECO1000

Smoke and Thermal Detectors



FEATURES

Photo-thermal model

Laser-based remote test unit

EN 54 Certified (2000 edition)

Photoelectric, photo-thermal and thermal detectors

Improved chamber design

Compatible with fire and security systems

-20 to +60°C operating temperature range

Choice of bases (including a 12V relay version)

Photoelectric model with integral piezoelectric sounder
(availability subject to further announcement)



ECO1000

Smoke and Thermal Detectors

SPECIFICATIONS

Dimensions:	42mm (optical) or 50mm (thermal) ø 102mm	
Operating Voltage:	8 – 30VDC (nominal 12 or 24VDC)	
ECO Bases:	ECO1000B	Standard base
	ECO1000BSD	Standard base with Schottky diode
Accessories	ECO1000RTU	Remote test unit
Part Numbers:	Optical + base	ECO 1003 + Base
	Optical	ECO 1003
	Optical thermal + base	ECO 1002 + Base
	Optical thermal	ECO 1002
	Standard base	ECO 1000B
	Diode base	ECO 1000BSD
	Thermal + base	ECO 1005 + Base
	Thermal	ECO 1005

ECO1002 COMBINED PHOTO THERMAL

Typical Standby Current:	240µA
Maximum Alarm Current:	50mA (limited by control panel)
Maximum Humidity:	95% RH
Operating Temperature:	-20 to +60°C
Weight:	75g
Approvals:	Meets EN54-7:2000; EN54-5:2000 Class A1R; CEA4021

ECO1003 PHOTO-ELECTRIC DETECTOR

Typical Standby Current:	110µA
Maximum Alarm Current:	50mA (limited by control panel)
Maximum Humidity:	95% RH
Operating Temperature:	-20 to +60°C
Weight:	75g
Approvals:	Meets EN54-7:2000

ECO1005 RATE OF RISE THERMAL DETECTOR

Typical Standby Current:	125µA
Maximum Alarm Current:	50mA (limited by control panel)
Maximum Humidity:	95% RH
Operating Temperature:	-20 to +60°C
Weight:	70g
Approvals:	Meets EN54-5:2000 Class A1R

ORDERING